Application No.: 09/348,494 Old Attorney's Docket No. 040070-244 New Attorney's Docket No. 0119-016 Page 2

Amendments to the Claims:

Please replace all prior versions, and listings of claims in the application with the following listing of claims.

Listing of claims

Claims 1 and 2 (canceled)

Claim 3 (previously presented): A mobile station comprising:

- a first antenna;
- a first radio frequency processing circuit receiving and processing signals from said first antenna;
 - a second antenna:
- a second radio frequency processing circuit receiving and processing signals from said second antenna; and

a base band processing circuit receiving processed radio frequency signals from said first radio frequency processing circuit and from said second radio frequency processing circuit for diversity, and providing a control signal to said second radio frequency processing circuit to selectively activate and deactivate said second radio frequency processing circuit based on a determination as to whether diversity is appropriate, wherein said control signal generated by said base band processing circuit is controlled by a control signal from a base station with which said mobile station is in communication.

Claim 4 (original): A mobile station in accordance with claim 3 wherein the base station will increase or decrease its output power to said mobile station after transmitting said control signal until a sufficient signal quality of the communication link.

Claim 5 (previously presented): A mobile station comprising:

- a first antenna:
- a first radio frequency processing circuit receiving and processing signals from said first antenna:
 - a second antenna;

Application No.: 09/348,494
Old Attorney's Docket No. 040070-244
New Attorney's Docket No. 0119-016
Page 3

a second radio frequency processing circuit receiving and processing signals from said second antenna; and

a base band processing circuit receiving processed radio frequency signals from said first radio frequency processing circuit and from said second radio frequency processing circuit for diversity, and providing a control signal to said second radio frequency processing circuit to selectively activate and deactivate said second radio frequency processing circuit based on a determination as to whether diversity is appropriate, wherein said mobile station informs a base station of its deactivation of diversity so that the base station will adjust its output power until a sufficient signal quality is achieved in accordance with the non-diversity mode.

Claims 6-13 (canceled)

Claim 14 (previously presented): A method of controlling diversity in a mobile station, comprising:

receiving a radio signal on a first antenna;

processing radio signals from said first antenna in a first radio frequency processing circuit;

receiving radio signals in a second antenna;

processing radio signals from the second antenna in a second radio frequency processing circuit;

receiving processed radio frequency signals from said first radio frequency processing circuit and from said second radio frequency processing circuit for diversity in a base band processing circuit;

determining whether diversity is appropriate; and

providing a control signal to said second radio frequency processing circuit to selectively activate and deactivate said second radio frequency processing circuit based on said determination as to whether diversity is appropriate,

further comprising controlling the generation by said base band processing circuit of said control signal by a control signal from a base station with which said mobile station is in communication.

Application No.: 09/348,494
Old Attorney's Docket No. 040070-244
New Attorney's Docket No. 0119-016
Page 4

Claim 15 (original): A method in accordance with claim 14 further comprising adjusting an output power of the base station to said mobile station after transmitting said control signal until a sufficient signal quality of the communication link.

Claim 16 (previously presented): A method of controlling diversity in a mobile station, comprising:

receiving a radio signal on a first antenna;

processing radio signals from said first antenna in a first radio frequency processing circuit;

receiving radio signals in a second antenna;

processing radio signals from the second antenna in a second radio frequency processing circuit;

receiving processed radio frequency signals from said first radio frequency processing circuit and from said second radio frequency processing circuit for diversity in a base band processing circuit;

determining whether diversity is appropriate; and

providing a control signal to said second radio frequency processing circuit to selectively activate and deactivate said second radio frequency processing circuit based on said determination as to whether diversity is appropriate, further comprising said mobile station informing a base station of its deactivation of diversity so that the base station will adjust its output power until a sufficient signal quality is achieved in accordance with the non-diversity mode.

Claims 17-20 (canceled)